



VULCANO INSULATED HALF-PIPE HEAT AND ENGINEERING FOR YOUR ROAD



CONSTRUCTION



TRANSPORTED MATERIAL

- Asphalt
- Asphalt debris

CHASSIS



BODY

- Hardox





PRODUCED VERSIONS (*p.15)

VOLUME	INTERNAL LENGTH	SIDEBORD HEIGHT	LOAD HEIGHT	DOOR DEGREES	REAR EXTENSION*	WALLS FINISHING**	N° OF WHEELS
23,5 m³	7,450 mm	1,440 mm	2,930 mm	20°	200 mm	IS/LZ/LS	6
26,5 m³	7,450 mm	1,640 mm	2,895 mm	20°	200 mm	IS/LZ/LS	6
30 m³	7,450 mm	1,840 mm	3,295 mm	20°	200 mm	IS/LZ/LS	6
24 m³	7,450 mm	1,440 mm	2,930 mm	90°	200 mm	IS/LZ/LS	6
27,5 m³	7,450 mm	1,640 mm	2,895 mm	90°	200 mm	IS/LZ/LS	6
31 m³	7,450 mm	1,840 mm	3,295 mm	90°	200 mm	IS/LZ/LS	6

*optional

**IS mirror stainless steel finishing - LZ painted galvanized sheet finishing - LS brushed metal sheet finishing

26



LIFT AXLES



Unloading hatch



DOOR

B

Tilting



Hydraulic



TARPAULINS

- Tarpaulin body height
- Semi-hermetic tarpaulin
- Hermetic tarpaulin





OPTIONAL ACCESSORIES

- Mirror/galvanized finish
- Various types of tarpaulin
- Polyurethane tarpaulin
- Lift axles
- Steering wheel
- Hatch on rear door
- Door closing with mechanical hooks
- Pneumatic underrun bar
- BPW Thermo Monitor
- Broom and shovel kit
- ADR kit
- Imo/(Rina) approved ferry hooks kit
- Rock version
- Pneumatic nebulizer
- Rear extension

