



SATURNO SQUARE-BODY TECHNOLOGY APPLIED TO AGRICULTURE AND ECOLOGY



AGRO, RECYCLING



TRANSPORTED MATERIAL

- Agricultural products
- Bulk products
- Wood chips
- Pallet
- Cereals
- Big bag
- Fertilizers
- Wood
- Waste
- Glass

CHASSIS



BODY

- Aluminium
- Tipperlite® Aluminium
- Endur-Al





PRODUCED VERSIONS (*p.15)

VOLUME	INTERNAL LENGTH	SIDEBORD HEIGHT	LOAD HEIGHT	DOOR TYPE	DOOR DEGREES	CHASSIS TYPE
740R I65						
42.5 m ³	7,720 mm	2,200 mm	3,815 mm	G	90°	SA/SL
900R I65						
41 m ³	9,200 mm	1,800 mm	3,435 mm	FG/G	90°	SL
46 m ³	9,200 mm	2,000 mm	3,635 mm	FG/G	90°	SL
51 m ³	9,200 mm	2,200 mm	3,835 mm	G	90°	SL
850R I65						
41 m ³	9,200 mm	1,800 mm	3,370 mm	FG/G	90°	SA
46 m ³	9,200 mm	2,000 mm	3,570 mm	FG/G	90°	SA
51 m ³	9,200 mm	2,200 mm	3,770 mm	G	90°	SA
105R I65						
40 m ³	10,500 mm	1,600 mm	3,262 mm	FG/G	90°	SA/SL
46 m ³	10,500 mm	1,800 mm	3,462 mm	FG/G	90°	SA/SL
52 m ³	10,500 mm	2,000 mm	3,662 mm	FG/G	90°	SA/SL
57 m ³	10,500 mm	2,200 mm	3,862 mm	G	90°	SA/SL

*The charge height indicated in the table refers to the SL model, the charge height for the SA model is 40 mm lower

DOOR

C

Universal door with crossmember



D

Two doors with crossmember



F

Tilting double pin



FG

Tilting with gasket



Hydraulic with gasket



G

Hermetic tilting door

Hermetic side door





PRODUCED VERSIONS (*p.15)

VOLUME	INTERNAL LENGTH	SIDEBOARD HEIGHT	LOAD HEIGHT	DOOR TYPE	DOOR DEGREES	CHASSIS TYPE
105R I65						
42.5 m ³	11,050 mm	1,600 mm	3,262 mm	FG/G	90°	SA/SL
48.5 m ³	11,050 mm	1,800 mm	3,462 mm	FG/G	90°	SA/SL
54 m ³	11,050 mm	2,000 mm	3,662 mm	FG/G	90°	SA/SL
60 m ³	11,050 mm	2,200 mm	3,862 mm	G	90°	SA/SL
740R I30						
44 m ³	7,720 mm	2,200 mm	3,830 mm	C/D/F	90°	SA/EXL
900R I30						
42 m ³	9,200 mm	1,800 mm	3,385 mm	C/D/F	90°	EXL
47 m ³	9,200 mm	2,000 mm	3,585 mm	C/D/F	90°	EXL
52 m ³	9,200 mm	2,200 mm	3,785 mm	C/D/F	90°	EXL

*The charge height indicated in the table refers to the SL model, the charge height for the SA model is 40 mm lower



TARPAULINS

MOD. I65 AND I30

Hermetic tarpaulin - standard closure



Tarpaulin body height - rear crescent-shaped closure



Semi-hermetic tarpaulin - automatic closure autoback





PRODUCED VERSIONS (*p.15)

VOLUME	INTERNAL LENGTH	SIDEBOARD HEIGHT	LOAD HEIGHT	DOOR TYPE	DOOR DEGREES	CHASSIS TYPE
--------	-----------------	------------------	-------------	-----------	--------------	--------------

850R I30

42 m ³	9,200 mm	1,800 mm	3,370 mm	C/D/F	90°	SA
47 m ³	9,200 mm	2,000 mm	3,570 mm	C/D/F	90°	SA
52 m ³	9,200 mm	2,200 mm	3,770 mm	C/D/F	90°	SA

105R I30

42.5 m ³	10,500 mm	1,600 mm	3,180 mm	C/D/F	90°	SA/EXL
48 m ³	10,500 mm	1,800 mm	3,380 mm	C/D/F	90°	SA/EXL
53.5 m ³	10,500 mm	2,000 mm	3,580 mm	C/D/F	90°	SA/EXL
59 m ³	10,500 mm	2,200 mm	3,780 mm	C/D/F	90°	SA/EXL

105R I30

50.5 m ³	11,050 mm	1,800 mm	3,380 mm	C/D/F	90°	SA/EXL
56 m ³	11,050 mm	2,000 mm	3,580 mm	C/D/F	90°	SA/EXL
62 m ³	11,050 mm	2,200 mm	3,780 mm	C/D/F	90°	SA/EXL

105R D30

52.5 m ³	10,625 mm	2,000 mm	3,585 mm	C/D/F	90°	SA/EXL
57.7 m ³	10,625 mm	2,200 mm	3,785 mm	C/D/F	90°	SA/EXL

*The charge height indicated in the table refers to the SL model, the charge height for the SA model is 40 mm lower



TARPAULINS

MOD. D30

Side - roll





OPTIONAL ACCESSORIES

- Lift axles
- Steering wheel
- Hatch on rear door
- ADR kit
- Imo/(Rina) approved ferry hooks kit
- Coil hole
- Vibrator
- Broom holder
- Tool box

