



GIOVE HALF-PIPE STRENGTH UNDER CONTROL

CONSTRUCTION



TRANSPORTED MATERIAL

- Sand
- Soil
- Clay
- Gravel
- Small rocks
- Big rocks
- Asphalt waste
- Mud

CHASSIS



BODY

- Aluminium
- Hardox
- Endur-Al
- Tipperlite®
Aluminium



SA740R



SA740M



SA742R





PRODUCED VERSIONS (*p.15)

VOLUME	INTERNAL LENGTH	SIDEBOARD HEIGHT	LOAD HEIGHT	DOOR TYPE	DOOR DEGREES	REAR EXTENSION**	N° OF WHEELS
--------	-----------------	------------------	-------------	-----------	--------------	------------------	--------------

SA700R

23,5 m³	7,450 mm	1,440 mm	2,930 mm	B	20°	200 mm	6
26,5 m³	7,450 mm	1,640 mm	2,895 mm	B	20°	200 mm	6
30 m³	7,450 mm	1,840 mm	3,295 mm	B	20°	200 mm	6
24 m³	7,450 mm	1,440 mm	2,930 mm	FG/G/CU	90°	200 mm	6
27,5 m³	7,450 mm	1,640 mm	2,895 mm	FG/G/CU	90°	200 mm	6
31 m³	7,450 mm	1,840 mm	3,295 mm	FG/G/CU	90°	200 mm	6

SA700G

23,5 m³	7,450 mm	1,440 mm	2,930 mm	B	20°	200 mm	10
26,5 m³	7,450 mm	1,640 mm	3,130 mm	B	20°	200 mm	10
29,5 m³	7,450 mm	1,840 mm	3,330 mm	B	20°	200 mm	10

** optional

DOOR

B

Tilting



Hydraulic



FG

Tilting with gasket



Hydraulic with gasket




G

Hermetic tilting door



Hermetic side door



CU

Tilting



Two doors





PRODUCED VERSIONS*

VOLUME	INTERNAL LENGTH	SIDEBOARD HEIGHT	LOAD HEIGHT	DOOR TYPE	DOOR DEGREES	REAR EXTENSION**	N° OF WHEELS
--------	-----------------	------------------	-------------	-----------	--------------	------------------	--------------

SA740R

28 m ³	7,600 mm	1,640 mm	3,095 mm	FG/G	90°	200 mm	6
32 m ³	7,600 mm	1,840 mm	3,295 mm	FG/G	90°	200 mm	6
36 m ³	7,600 mm	2,040 mm	3,495 mm	FG/G	90°	200 mm	6

SA740M

23,5 m ³	7,450 mm	1,440 mm	2,930 mm	B	20°	200 mm	8
26,5 m ³	7,450 mm	1,640 mm	2,895 mm	B	20°	200 mm	8
30 m ³	7,450 mm	1,840 mm	3,530 mm	B	20°	200 mm	8

SA742R

26,5 m ³	7,500 mm	1,640 mm	3,220 mm	B	20°	-	4
---------------------	----------	----------	----------	---	-----	---	---

*Sizes and volumes are provided by way of indicative title and may vary depending on of the chosen model and configuration. The data indicated are calculated in compliance to the European Regulation 1230/2012

** optional



TARPAULINS

Semi-hermetic tarpaulin



Automatic closure autoback



Tarpaulin body height



Standard closure



Tarpaulin integro



Cantilever double arch closure





PRODUCED VERSIONS (*p.15)

VOLUME	INTERNAL LENGTH	SIDEBOARD HEIGHT	LOAD HEIGHT	DOOR TYPE	DOOR DEGREES	REAR EXTENSION**	N° OF WHEELS
--------	-----------------	------------------	-------------	-----------	--------------	------------------	--------------

SA850R

28 m³	9,000 mm	1,440 mm	2,928 mm	B	23°	200 mm	6
32 m³	9,000 mm	1,640 mm	3,128 mm	B	23°	200 mm	6
36 m³	9,000 mm	1,840 mm	3,328 mm	B	23°	200 mm	6
29 m³	9,000 mm	1,440 mm	2,928 mm	FG/G	90°	200 mm	6
33.5 m³	9,000 mm	1,640 mm	3,128 mm	FG/G	90°	200 mm	6
38 m³	9,000 mm	1,840 mm	3,328 mm	FG/G	90°	200 mm	6

SL740R EXL

24 m³	7,700 mm	1,440 mm	2,970 mm	B	15°	240 mm	6
28 m³	7,700 mm	1,640 mm	3,170 mm	B	15°	240 mm	6
31.5 m³	7,700 mm	1,846 mm	3,370 mm	B	15°	240 mm	6

** optional



LIFT AXLES



HOOKS FOR TARPAULIN

with Z-shaped profile



with wheels





OPTIONAL ACCESSORIES

- Lift axles
- Steering wheel
- Pneumatic underrun bar
- Hatch on rear door
- Door closing with mechanical hooks
- Broom and shovel kit
- ADR kit
- Imo/(Rina) approved ferry hooks kit
- Rock version
- Pneumatic nebulizer
- Rear extension

